



Specifications		MS8332C
Specifications	Range	Accuracy
DC Voltage	400mV/4V/40V/400V	±(0.8%+3)
	600V	±(1.0%+5)
AC Voltage	4V/40V/400V	±(1.0%+3)
	600V	±(1.5%+5)
DC Current	400uA/4mA/40mA/400mA	±(1.8%+5)
AC Current	400uA/4mA/40mA/400mA	±(2.0%+5)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ	±(1.0%+3)
	400MΩ	±(1.2%+15)
Capacitance	4nF	±(5.0%+0.6)
	40nF/400nF	±(4.0%+15)
	4μF/40μF/100μF	±(5.0%+25)
Frequency	10~5MHz	±(1.5%+15)
Duty Cycle	5%~95%	±(2.0%+5)
Battery Test	1.5V/9V	±(2.0%+20)
Features		
Display	counts	6000
Auto Ranging	Auto & Manual	●
APO	Auto Power Off	●
Diode	2.7V	●
Continuity Buzzer	<50Ω	●
Data Hold		●
Backlight		●
LBD	Low Battery Display	●
General		
Power Supply	2×1.5V AAA Batteries	
Product Size	122mm×61mm×41mm/4.8"×2.4"×1.6"	
Product Weight	183g/0.4lb	
Safety Rating	CE ETL CAT.III 600V RoHS	



MS8332C

VOLTAGE AC 600V
DC 600V

CURRENT AC 400mA
DC 400mA

