


Small Signal Schottky Diode

Features

- V_R 60V/50V/40V
- I_{FAV} 70mA



Mechanical Data

- **Package:** SOD323
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

	Marking
SD101AWS	S1
SD101BWS	S2
SD101CWS	S3

■ Maximum Ratings ($T_a=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Conditions	VALUE	
Reverse voltage	V_R	V	$I_R=10\mu\text{A}$	SD101AWS	60
				SD101BWS	50
				SD101CWS	40
Average forward current	I_{FAV}	mA	$T_c=25^\circ\text{C}$	70	
Power dissipation	P_D	mW		200	
Maximum junction temperature	T_j	$^\circ\text{C}$		-55 to +125	
Storage temperature range	T_{stg}	$^\circ\text{C}$		-55 to +150	
Thermal Resistance Junction to Ambient Air	$R_{\theta JA}$	$^\circ\text{C/W}$		500	

■ Electrical Characteristics ($T_a=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Conditions	VALUE	
Maximum Forward voltage	V_F	V	$I_F=1\text{mA}, T_A=25^\circ\text{C}$	SD101AWS	0.41
				SD101BWS	0.4
				SD101CWS	0.39
	V_F	V	$I_F=15\text{mA}, T_A=25^\circ\text{C}$	1.0	
Maximum Reverse current	I_R	μA	SD101AWS	$V_R=50\text{V}, T_A=25^\circ\text{C}$	0.2
			SD101BWS	$V_R=40\text{V}, T_A=25^\circ\text{C}$	
			SD101CWS	$V_R=30\text{V}, T_A=25^\circ\text{C}$	
Minimum Breakdown voltage	$V_{(BR)}$	V	$I_R=10\mu\text{A}$	SD101AWS	60
				SD101BWS	50
				SD101CWS	40
Maximum Junction capacitance	C_J	pF	$V_R=1\text{V}, f=1\text{MHz}$	2	







SD101AWS THRU SD101CWS

Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SD101AWS Thru SD101CWS	F2	Approximate 0.004	3000	30000	120000	7" reel


Characteristics (Typical)






SD101AWS THRU SD101CWS

■ Outline Dimensions



Symbol	Min. (mm)	Max. (mm)
A		1.000
A1	0.000	0.100
A2	0.800	0.900
b	0.250	0.400
c	0.080	0.150
D	1.200	1.400
E	1.600	1.800
E1	2.500	2.700
L	0.475REF	
L1	0.250	0.400
θ	0°	8°

■ Soldering Footprint





SD101AWS THRU SD101CWS

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.